

**UltraPoxy** – Part B

# Safety Data Sheet

Issued Date: 1/02/2022 Revision Date: 6/09/2023 Issued by: Online Paints Ltd



## **1. IDENTIFICATION**

GHS Product Identifier UltraPoxy - Part B Product Code(s) BOSS16501b

Company Name Online Paints Limited

Address 42 Ototara Lane, RD2, Wellsford, 0972

**Telephone** Telephone: +64 274 783 001 Emergency phone number +64 274 783 001 (8:00am – 5pm Monday to Friday)

E-mail Address sales@onlinepaints.co.nz

Recommended use of the chemical and restrictions on use Industrial application

## 2. HAZARD IDENTIFICATION

## GHS classification of the substance/mixture

HSNO Status: Classified as hazardous according to the criteria of HSNO. DG Status: Classified as Dangerous Goods according to NZS5433. Signal Word: Danger

HSNO Code	HSNO classifications	Hazard statements	GHS Pictogram
6.1D (oral)	acute oral toxicity Category 4	H302 - Harmful if swallowed.	$\diamondsuit$
6.1D (dermal)	acute dermal toxicity Category 4	H312 - Harmful in contact with skin.	
8.2C	skin corrosion Category 1C	H314 - Causes severe skin burns and eye damage.	Red A
6.5B	skin sensitisation Category 1	H317 - May cause an allergic skin reaction.	
8.3A	serious eye damage Category 1	H318 - Causes serious eye damage.	Real Provide Action of the second sec
9.1C	hazardous to the aquatic environment chronic Category 3	H412 - Harmful to aquatic life with long lasting effects.	

9.2B	hazardous to soil organisms	H422 - Toxic to the soil environment.	
9.3C	hazardous to terrestrial vertebrates	H433 - Harmful to terrestrial vertebrates.	

## Precautionary Statements

- recaulionary ola		
General		
P101	If medical advice is needed, have product container or label at hand.	
P102	Keep out of reach of children.	
P103	Read label before use.	
Prevention		
P260	Do not breathe dust/fume/gas/mist/vapours/spray.	
P264	Wash thoroughly after handling.	
P270	Do not eat, drink or smoke when using this product.	
P272	Contaminated work clothing should not be allowed out of the workplace.	
P273	Avoid release to the environment.	
P280	Wear protective gloves/protective clothing/eye protection/face protection.	
Response		
P301+P312	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.	
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.	
P302+P352	IF ON SKIN: Wash with plenty of soap and water.	
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.	
P304+P340	IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P310	Immediately call a POISON CENTER or doctor/physician.	
P312	Call a POISON CENTER or doctor/physician if you feel unwell.	
P330	Rinse mouth.	
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.	
P363	Wash contaminated clothing before reuse.	
P391	Collect spillage.	
Storage	·	
P405	Store locked up.	
Disposal		
P501	Do not let this product enter the environment. Do not dispose of in waterways or sewers. Dispose of this material and its container as hazardous waste, via a licensed facility. See local council for disposal/recycling information.	

## **3. COMPOSITION / INFORMATION ON INGREDIENTS**

## Ingredients

Name	CAS	Proportion - %w/w
Isophorone diamine	2855-13-2	30-60
Benzyl alcohol	100-51-6	30-60
Cashew nutshell extract	8007-24-7	10-30
Mannich base	90-72-2/71074-89-0	1-10
Epoxy resin	28064-14-4	1-10
Ingredients determined not to be hazardous or below the hazardous threshold.		То 100%

Preparation Description - Epoxy hardener

## 4. FIRST-AID MEASURES

### Inhalation

If inhaled, remove affected person from contaminated area. Keep at rest until recovered. If symptoms develop and/or persist seek medical attention.

#### Ingestion

Do not induce vomiting. Wash out mouth thoroughly with water. Seek medical attention.

#### Skin

Wash affected area thoroughly with soap and water. If symptoms develop seek medical attention.

### Eye contact

If in eyes, hold eyes open and flush continuously. Continue flushing for several minutes until all contaminants are completely removed. If symptoms develop and/or persist seek medical attention.

### **First Aid Facilities**

Eyewash and normal washroom facilities.

#### Advice to Doctor Treat symptomatically

For advice in an emergency, contact the National Poisons Centre (0800 764 766), or a doctor, at once.

## 5. FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

Carbon dioxide, dry chemical, foam, water fog or water mist.

## **Unsuitable Extinguishing**

Water with full jet.

### **Hazards from Combustion Products**

Toxic products may be given off in a fire.

## **Decomposition Temperature**

Not available

### **Precautions in connection with Fire**

Fire fighters should wear full protective clothing and self-contained breathing apparatus (SCBA) operated in positive pressure mode. Fight fire from safe location.

## 6. ACCIDENTAL RELEASE MEASURES

### **Emergency Procedures**

Increase ventilation. If possible, contain the spill. Wear appropriate personal protective equipment and clothing to prevent exposure. Spillage can be slippery. Place inert absorbent material onto spillage. Collect the material and place into a suitable labelled container. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations. Dispose of waste according to the applicable local and national regulations.

## 7. HANDLING AND STORAGE

### **Precautions for Safe Handling**

Use only in a well-ventilated area. Keep containers tightly closed. Prevent the buildup of dusts, mists or vapours in the work atmosphere. Maintain high standards of personal hygiene i.e., washing hands prior to eating, drinking, smoking or using toilet facilities.

### Conditions for safe storage, including any incompatibilities

Protect from freezing. Store in a cool, dry, well-ventilated area, out of direct sunlight. Store in suitable, labelled containers. Ensure that storage conditions comply with applicable local and national regulations.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### **Occupational exposure limit values**

Not available

### **Biological Limit Values**

No biological limits allocated.

#### **Appropriate Engineering Controls**

Use with good general ventilation. If mists or vapours are produced, local exhaust ventilation should be used.

### **Respiratory Protection**

If engineering controls are not effective in controlling airborne exposure, then an approved respirator with a replaceable vapor/mist filter should be used. If engineering controls are not effective in controlling airborne exposure, then an approved respirator with a replaceable vapor/mist filter should be used. Reference should be made to Australia/New Zealand Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

### **Eye Protection**

Safety glasses with side shields, chemical goggles, or full-face shield as appropriate should be used. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform to relevant regulations. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.

### **Hand Protection**

Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances i.e., methods of handling or according to risk assessments undertaken. Occupational protective gloves should conform to relevant regulations. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

### **Body Protection**

Suitable protective workwear, e.g., cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Form Liquid

**Colour** Yellow/Straw

Odour Mild

Decomposition Temperature Not available

Melting Point Not available

Boiling Point Not available

Solubility in Water Soluble

Specific Gravity 1.00-1.10

**pH when packed** Not applicable

Vapour Pressure Not available

Vapour Density (Air=1) Not available Evaporation Rate Not available

Odour Threshold Not available

Partition Coefficient: n-octanol/water Not available

Flash Point Not applicable

Flammability Non-combustible material

Auto-Ignition Temperature Not applicable

Flammable Limits - Lower Not applicable

Flammable Limits - Upper Not applicable

Kinematic Viscosity Not available

Dynamic Viscosity Not available

Freeze thaw stability Stable

## **10. STABILITY AND REACTIVITY**

**Reactivity** Not expected to be a problem.

**Chemical Stability** Stable under normal conditions of storage and handling

Hazardous Decomposition Products Thermal decomposition may result in the release of toxic and/or irritating fumes. **Conditions to Avoid** Extremes of temperature and direct sunlight. P

**Incompatible materials** Strong oxidising agents. Strong acids and bases.

**Possibility of hazardous reactions** Not available

Hazardous Polymerization Will not occur.

## **11. TOXICOLOGICAL INFORMATION**

Original data sourced from raw material SDSs and/or CCID.

Acute Oral Toxicity	Harmful if swallowed.
Acute Dermal Toxicity	Harmful in contact with skin.
Acute Inhalation Toxicity	Not classified
Acute Aspiration Toxicity	Not classified
Skin Irritancy/Corrosion	Causes severe skin burns and eye damage.
Eye Irritancy/Corrosion	Causes severe skin burns and eye damage.
Respiratory Sensitisation	Not classified
Skin Sensitisation	May cause an allergic skin reaction.
Mutagenic	Not classified
Carcinogenic	Not classified
Reproductive/Development Toxicity	Not classified
STOT-SE	Not classified
STOT-RE	Not classified

Estimated Acute Toxicity -	product
----------------------------	---------

LD50 Oral: 1,199 mg/kg

LD50 Dermal: 1,524 mg/kg

LC50 Inhalation: >5 mg/L/4H

#### Ingestion

Ingestion of this product may irritate the gastric tract causing nausea and vomiting.

### Inhalation

Inhalation of product vapours may cause irritation of the nose, throat, and respiratory system.

### **Chronic Effects**

May cause an allergic skin reaction.

### Skin

May be irritating to skin. The symptoms may include redness, itching and swelling.

## Eye

May be irritating to eyes. The symptoms may include redness, itching and tearing.

## **12. ECOLOGICAL INFORMATION**

### Ecotoxicity

Ecotoxic according to criteria of HSNO.

Toxic to aquatic life with long lasting effects.

Product Calculated Ecotoxicity:  $LE(C)50 > 1 - \le 10 \text{ mg/L}$ 

#### **Ecotoxic Ingredients:**

Ingredient	Ecotoxic Classification
Isophorone diamine	9.1C - hazardous to the aquatic environment chronic Category 3
Benzyl alcohol	9.3A, 9.3B, 9.3C - hazardous to terrestrial vertebrates
Epoxy resin	9.1B - hazardous to the aquatic environment chronic Category 2

### Toxicity

Product Calculated Aquatic Ecotoxicity – L(E)C50: >100 mg/L

### Persistence and degradability

Not available

### Mobility

Not available

### Bioaccumulative Potential Not available

Other Adverse Effects Not available

**Environmental Protection** Prevent this material entering waterways, drains and sewers.

## **13. DISPOSAL CONSIDERATIONS**

### **Disposal considerations**

The disposal of the spilled or waste material must be done in accordance with applicable local and national regulations.

#### Product Disposal

This product can be disposed through a licensed commercial waste collection service. Product wastes are controlled wastes and should be disposed of in accordance with all applicable local and national regulations. This is a water-based/water-soluble product and therefore can be sent through a Wastewater Treatment Plant and after treatment can be discharged into environment through the sewerage or drainage systems as authorized. Personal protective clothing and equipment as specified in Section 8 of this SDS must be worn during handling and disposal of this product. The ventilation requirements as specified in the same section must also be followed, and the precautions given in Section 7 of this SDS regarding handling must also be followed. Do not dispose into the sewerage system. Dispose of waste according to applicable local and national regulations. In New Zealand, the disposal agency or contractor must comply with the New Zealand Hazardous Substances (Disposal) Regulations 2001. Further details regarding disposal can be obtained on the ERMA New Zealand website under specific group standards.

#### Container Disposal

The container or packaging must be cleaned and rendered incapable of holding any substance. It can then be disposed of in a manner consistent with that of the substance it contained. In this instance the packaging can be disposed through a commercial waste collection service. Alternatively, the container or packaging can be recycled if the hazardous residues have been thoroughly cleaned or rendered non-hazardous. In New Zealand, the packaging (that may or may not hold any residual substance) that is lawfully disposed of by householders or other consumers through a public or commercial waste collection service is a means of compliance with regulations.

## **14. TRANSPORT INFORMATION**

### **Transport Information**

Classified as Dangerous Goods for transport according to the New Zealand Standard NZS 5433:2007 Transport of Dangerous Goods on Land.

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

Regulated for transport	Keep separated from foodstuffs
UN Number:	3267
Proper Shipping Name:	Corrosive liquid, basic, organic, n.o.s.
Class:	8
Packing Group:	III
Hazchem:	2X
CORROSIVE	

## **15. REGULATORY INFORMATION**

#### **Regulatory information**

8

Classified as Hazardous according to the criteria of HSNO.

Group Standard:	HSR002658 Surface Coatings & Colorants (Corrosive) Group Standard 2020	
HSNO CONTROLS		
SDS required when any quantity Is present in a workplace.		
Emergency Response Plan And Secondary Containment required when >1,000L is present in a workplace.		
Toxic signage required when storing >10,000L is stored.		
Corrosive signage required when >1,000L is s	tored.	
Ecotoxic signage required when >1,000L is sto	ored.	
Certified Handler	Not Required	
Tracking	Not Required	
All ingredients are on the New Zealand Invent	ory of Chemicals (NZIOC), or exempt.	

Any existing national regulations on the handling of dangerous substances should be observed. Controls for hazardous substances are based upon current knowledge. Where multiple chemicals are stored, controls will need to take into account aggregate quantities. Contact a WorkSafe approved Compliance Certifier for further information and guidance.

## **16. OTHER INFORMATION**

## **Contact Person / Point**

IMPORTANT ADVICE: This SDS summarises our best knowledge of the health and safety hazard information of the product and how to safely handle and use the product in the workplace. Each user should read this SDS and consider the information in the context of how the product will be handled and used in the workplace including its use in conjunction with other products. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact the supplier listed in section 1 of the SDS. Our responsibility for products sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available on request.

### **Technical Contact Numbers**

For further information, contact Online Paints Ltd on +64 274 783001, however, in emergencies contact National Poisons Centre (0800 764 766).

### Glossary

HSNO = Hazardous Substances and New Organisms Act 1996

- EPA = Environmental Protection Authority (NZ)
- CCID = Chemical Classification & Identification Database (EPA)
- WES = NZ Work Exposure Standard
- TWA = Time Weighted Average
- STEL = Short Term Exposure Limit